

Machine Name : CNC lathe

Brand : HYUNDAI KIA

Machine Model : SKT28L

Stock No. : 470490

Ex-factory Date :



Main Technical Parameters:

Maximum turning diameter over bed 590 mm

Rapid feed rate (X * Z * C axis) 20 * 24 m/min

Maximum machining diameter 410 mm

Feed rate(X * Z axis) 220 * 1100 mm

Standard chuck size 254 [305] mm

Tailstock sleeve taper hole MT # 5

Maximum workpiece length 1070 mm

Tailstock travel 920 mm

Maximum bar diameter 76 [80] mm

Spindle speed 3000 rpm

Diameter of spindle through hole 95 mm

Spindle diameter (bearing) 130 mm

Spindle nose A2-8



主 轴	主轴通孔直径		mm	Ø95	
	主轴速度 (rpm)		rpm	3,000 [3,000]	
	电机功率 (最大连续)		kW	22/18.5 [33.9/25]	
	扭矩 (最大连续)		Nm	729.5/13.5 [341.4/534.5]	41
	主轴形式		-	皮带	
	主轴脚踏		-	A2-B	
	C轴分度		deg	-	
进 给	行程 (X/Z)		mm	220/750	220/1,100
	快速移动速度 (X/Z)		m/min		25/30
	导轨类型		-		直线导轨
刀 库	刀具数量		EA	10 [12]	
	刀具尺寸	外径	mm		Ø25
		内径	mm		Ø50
	分度时间		sec/step		0.3
	电机功率 (最大连续)		kW	-	
动力刀具	动力刀具转速 (rpm)		rpm		
	扭矩 (最大连续)		Nm	-	
	夹头尺寸		mm		
	型号		-	-	
尺 寸	键座		-		MT5
	最大直径		mm		Ø100
	最大行程		mm		120
水箱自重	行程		mm	570	820
	冷却液箱		l	180	200
	重量/箱		kg		1.8
电源供应		kVA	24		



