

Machine Name : Surface grinder

Brand : Okamoto

Machine Model : ACC-350II

Stock No. : 92632

Ex-factory Date : There is no



Main Technical Parameters:

machining capacity: 360*150mm

Distance from Worktable top to bottom of grinding wheel: 297.5mm

Standard Chuck size: 350*150mm

Worktable load (including chuck) : 120kg

T-slot: 17*1mm


X*Y axis travel: 210*390mm

grinding wheel speed: 2900rpm

Machine Footage: 1555*1381*1918mm

Total Machine Footage: 740kg



功能	单位	A60-350 II	标准附件:
工作台	加工能力 (长度×宽度)	mm 360x150	- 砂轮 - 砂轮法兰 - 砂轮修整器 - 吸尘系统 - 调平螺钉和垫板 - 必备工具
	工作台面到砂轮下面的距离	mm 297.5	
	标准平台尺寸 (长×宽)	mm 350x150	
	工作承重能力 (包括组合)	kg 120	
	T型槽 (宽度×深度)	mm 17x1	
纵向进给	最大行程	mm 360	可选附件: - 微量纵向进给装置 - 微量垂直进给装置 - 冷却系统 - 安全防护罩及附件 - 主键罩帽器
	每转手动进给量	mm 100	
横向进给	最大行程	mm 210	
	每转手动进给量	mm 5.0	
	手轮刻度	mm 0.02	
垂直进给	每转手动进给量	mm 1.0	
	手轮刻度	mm 0.005	
砂轮	直径×宽度×厚度	mm 20.5x6-25x31.75	
	转速 (50Hz)	rpm 2900	
电机	砂轮轴	mm 1.5/2	
	吸尘喷嘴	mm 0.4/2	
占地面积	直径×宽度×高度	mm 440x1350x1915	
重量	净重	kg 740	

