

Machine Name : Vertical machining center

Brand : KITAMURA

Machine Model : Mycenter- 3XH

Stock No. : 488563

Ex-factory Date : 2016



Main Technical Parameters:

travel of X*Y*Z axis: 760*455*460mm

Worktable size: 410*900mm

Maximum load: 500kg

Spindle speed: 40- 15,000 RPM

spindle taper: NST.NO.40

spindle motor power: 15kw

spindle torque: 95.5Nm

Rapid feed rate: 50,000 mm/min

Chip feed rate: 0-36000mm/min

tools magazine :30

Distance from worktable to spindle nose is 110*570mm

machine tool weight: 5,740 kg

Appearance Footage: 2235*2370*2882.4mm





「天價發售」後日加「扣加」工資的報聞，引起「排排扣」事件。此間，「排扣」已屬笑話，反而「排排扣」成了笑話。

頁入初作：2733. 頁

转速范围: 20-2000rpm,

北机机械 Mycenter 3XiG/3XG		
工作台	工作尺寸/寸	4150×800 mm
	最大承重	5000 kg
	X/Z行程/寸	1020/450×460mm
工轴	主轴转速	205 ~ 2600
	最大承重	40×(5.000 mm)÷1
	工轴行程	1580mm
	主轴电机	65 kW
	主轴功率	主轴电机
刀库	刀库容量	8+2 (备刀)
	刀柄	MA5 DT30-40
	刀具交换时间 (T-TOOL)	1.5sec/3.5sec
	以标准转速换刀时间	50.000 mm/min
快速进给	快速进给速度 (Fmax)	55.000 mm/min
	切削进给速度	55.000 mm/min
	切削速度	55.000 mm/min
电源及气源要求	电源功率	50/2000VA=100% 200KVA
机床尺寸	机床尺寸 (W×D×H)	2,225×2,270×2,820 4mm
	机床重量	24,400kg
	控制系统	Automatic NC (三菱 M-7500)