Machine Name : Gantry machining center

Brand : AWEA

Machine Model : SP-3016

Stock No. : 66062

Ex-factory Date : 2018



Main Technical Parameters:

X-axis travel: 3060mm

Y-axis travel: 1600mm

Z-axis travel: 760mm

Distance between the two columns: 1700kg

Distance from spindle nose to workWorktable surface :200-960mm

WorkWorktable size: 3000x1500mm

The maximum load of workWorktable is 10,000 kg

Main motor power: 22/26 kW

Tool holder form: BT50 gear spindle

CNC System: FANUC oi-MD

Two linear guideways and one rigid guideway

PamtonSchnell













PamtonSchnell







雙柱間距離	1,700 mm		
工作台			
工作台尺寸 (X 方向)	2,310 mm	3,260 mm	4,200 mm
工作台尺寸 (Y 方向)	1,500 mm		
工作台載重量	8,000 kg	10,000 kg	12,000 kg
主軸			
主軸馬達 (連續 / 30 分)	22 / 26 kW (30 / 35 HP)		
主軸轉速	6,000 rpm ; 8,000 / 10,000 rpm 直結式主軸 (選配)		
主軸內孔規格	BT50 (ISO50) / DIN69871-A (選配)		
主軸進給			
快速進給速率 X 軸	20,000 mm / min.	20,000 mm / min.	15,000 mm / min.
快速進給速率 Y 軸	20,000 mm / min.		
快速進給速率 Z 軸	15,000 mm / min.		
切削進給速率	1 ~ 10,000 mm / min.		
刀庫			
刀庫容量	32 支刀 (60 / 90 / 120 選配)		
直徑 / 鄰刀空	Ø 127 / 215 mm		