

Machine Name : Boring and milling machine

Brand : KURAKI

Machine Model : KBT-15BA

Stock No. : 4810352

Ex-factory Date : 2002



Main Technical Parameters:

Three-axis travel: 3000*2300*1600mm

W-axis travel: 700mm

Worktable size: 2000*2200mm

Worktable indexing Angle: 0.001





Worktable load: 20,000 kg

Worktable slot spacing: 200mm

Spindle speed: 2000rpm









KURAKI K3T-15BA主要机械规格表

规格名称	单位	参数
机床型号		K3T-15BA
X轴行程	mm	3000
Y轴行程	mm	2300
Z轴行程	mm	1800
V轴行程	mm	700
油压枕	mm	150
旋转工作台尺寸	mm	2000*2200
工作台分度角度	度	0.001°
工作台承重	kg	20000
主轴转速	r/min	200
快速进给X/Y/Z轴	mm/min	2000
快速进给V轴	mm/min	8000
切削进给X/Y/Z轴	mm/min	4500
切削进给V轴	mm/min	1-4000
刀库容量	个	40
刀具选择方式		随机感应
主轴类型		BT50
最大刀具直径(满锥)	mm	Φ125
最大刀具直径(空锥)	mm	Φ240
最大刀具长度	mm	400
最大刀具重量	kg	25
攻牙特性		柔性攻丝
中心喷水(有/无)		无

来源: 曹勇 审核: [] 批准: []
日期: 25/05/2013 日期: [] 日期: []